



ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Issue date: 08/17/2026

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : ANTIQUE SANDALWOOD DUPLICATION
CAS-No. : MIXTURE
Product code : SC-AS

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Candles and Supplies
2580 Milford Square Pike
Quakertown PA 18951
215-538-8552
www.candlesandsupplies.com

1.4. Emergency telephone number

Emergency number : INFOTRAC (US & Canada) 1-800-535-5053 | (International) 1-352-323-3500

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 2 H315 Causes skin irritation.
Serious eye damage/eye irritation, Category 2 H319 Causes serious eye irritation.
Skin sensitization, Category 1 H317 May cause an allergic skin reaction.

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves.
P302+P352 - If on skin: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
BENZYL BENZOATE	(CAS-No.) 120-51-4	30 – 70	Acute Tox. 4 (Oral), H302
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone (Iso E Super)	(CAS-No.) 54464-57-2	10 – 30	Skin Irrit. 2, H315 Skin Sens. 1B, H317
2-Ethyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl)-2-buten-1-ol	(CAS-No.) 28219-61-6	1 – 5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
ETHYL VANILLIN	(CAS-No.) 121-32-4	1 – 5	Eye Irrit. 2B, H320
Dihydromyrcenol	(CAS-No.) 18479-58-8	1 – 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336
VANILLIN	(CAS-No.) 121-33-5	1 – 5	Eye Irrit. 2A, H319
COUMARIN	(CAS-No.) 91-64-5	1 – 5	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
2H-pyran-4-ol, tetrahydro-4-methyl-2-(2-methylpropyl)-	(CAS-No.) 63500-71-0	1 – 5	Eye Irrit. 2A, H319
CEDROL METHYL ETHER	(CAS-No.) 19870-74-7	1 – 5	Skin Sens. 1B, H317
3-methyl-5-(2,2,3-trimethyl-1-cyclopent-3-enyl)pentan-2-ol	(CAS-No.) 65113-99-7	1 – 5	Eye Irrit. 2A, H319
ETHOXYMETHYL CYCLODODECYL ETHER	(CAS-No.) 58567-11-6	1 – 5	Skin Irrit. 2, H315 Skin Sens. 1B, H317
LINALYL ACETATE	(CAS-No.) 115-95-7	1 – 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Skin Sens. 1B, H317
CITRAL	(CAS-No.) 5392-40-5	0.1 – 1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.

ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

- Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
- Methods for cleaning up : Take up liquid spill into absorbent material.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

- For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.
- Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Keep cool. Protect from sunlight.
- Packaging materials : Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

BENZYL BENZOATE (120-51-4)
Not applicable
2-Ethyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl)-2-buten-1-ol (28219-61-6)
Not applicable
LINALYL ACETATE (115-95-7)
Not applicable
ETHOXYMETHYL CYCLODODECYL ETHER (58567-11-6)
Not applicable
CEDROL METHYL ETHER (19870-74-7)
Not applicable

ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

CITRAL (5392-40-5)		
ACGIH	Local name	Citral
ACGIH	ACGIH® TLV® TWA	5 ppm (IFV - Inhalable fraction and vapor)
ACGIH	Remark (ACGIH®)	TLV® Basis: Body weight eff; URT irr; eye dam. Notations: Skin; DSEN; A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2024
COUMARIN (91-64-5)		
Not applicable		
Dihydromyrcenol (18479-58-8)		
Not applicable		
ETHYL VANILLIN (121-32-4)		
Not applicable		
2H-pyran-4-ol, tetrahydro-4-methyl-2-(2-methylpropyl)- (63500-71-0)		
Not applicable		
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8-tetramethyl-2-naphthalenyl)ethanone (Iso E Super) (54464-57-2)		
Not applicable		
3-methyl-5-(2,2,3-trimethyl-1-cyclopent-3-enyl)pentan-2-ol (65113-99-7)		
Not applicable		
VANILLIN (121-33-5)		
Not applicable		

8.2. Appropriate engineering controls

- Appropriate engineering controls
- : Ensure good ventilation of the work station.
- Environmental exposure controls
- : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state
- : Liquid
- Color
- : No data available
- Odor
- : No data available

ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 100 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
No data availableViscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: No data available
Acute toxicity (dermal)	: No data available
Acute toxicity (inhalation)	: No data available

BENZYL BENZOATE (120-51-4)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2 ml/kg (Modification of Draize 1959 method, 4 h, Rabbit, Experimental value, Dermal)
ATE US (oral)	1160 mg/kg body weight
2-Ethyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl)-2-buten-1-ol (28219-61-6)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, 2 week(s), Rat, Male/female, Experimental value, Oral)
LD50 dermal rat	> 5 ml/kg (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value, Dermal)

ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

ETHOXYMETHYL CYCLODODECYL ETHER (58567-11-6)	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 5000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male/female, Experimental value, Dermal, 14 day(s))

COUMARIN (91-64-5)	
LD50 oral rat	293 mg/kg body weight (Rat, Male / female, Experimental value, Oral)
ATE US (oral)	293 mg/kg body weight

ETHYL VANILLIN (121-32-4)	
LD50 oral rat	> 3160 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
ATE US (oral)	3000 mg/kg body weight

VANILLIN (121-33-5)	
LD50 oral rat	3300 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
ATE US (oral)	3300 mg/kg body weight
ATE US (dermal)	2600 mg/kg body weight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: No data available
Carcinogenicity	: No data available

COUMARIN (91-64-5)	
IARC group	3 - Not classifiable

Reproductive toxicity	: No data available
STOT-single exposure	: No data available

Dihydromyrcenol (18479-58-8)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure	: No data available
------------------------	---------------------

Aspiration hazard	: No data available
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

BENZYL BENZOATE (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (EU Method C.1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	3.09 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

2-Ethyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl)-2-buten-1-ol (28219-61-6)	
LC50 - Fish [1]	1.1 mg/l (US EPA, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, GLP)
ErC50 algae	2.5 mg/l (US EPA, 96 h, Selenastrum capricornutum, Static system, Fresh water, Experimental value, GLP)

LINALYL ACETATE (115-95-7)	
LC50 - Fish [1]	11 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Cyprinus carpio)
EC50 - Crustacea [1]	15 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna)

ETHOXYMETHYL CYCLODODECYL ETHER (58567-11-6)	
LC50 - Fish [1]	1.9 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	1.6 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

COUMARIN (91-64-5)	
LC50 - Fish [1]	2.94 mg/l (96 h, Pisces, QSAR)
EC50 - Crustacea [1]	24.3 – 36.9 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

ETHYL VANILLIN (121-32-4)	
LC50 - Fish [1]	87.6 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 - Crustacea [1]	36.79 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Read-across, GLP)
ErC50 algae	120 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)

VANILLIN (121-33-5)	
LC50 - Fish [1]	57 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 - Crustacea [1]	36.79 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	120 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

BENZYL BENZOATE (120-51-4)	
Persistence and degradability	Readily biodegradable in water.

2-Ethyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl)-2-buten-1-ol (28219-61-6)	
Persistence and degradability	Not readily biodegradable in water.
ThOD	3 g O ₂ /g substance

LINALYL ACETATE (115-95-7)	
Persistence and degradability	Readily biodegradable in water.

ETHOXYMETHYL CYCLODODECYL ETHER (58567-11-6)	
Persistence and degradability	Biodegradability in soil: no data available. Not readily biodegradable in water.

COUMARIN (91-64-5)	
Persistence and degradability	Readily biodegradable in water.

Dihydromyrcenol (18479-58-8)	
Persistence and degradability	Biodegradability in water: no data available.

ETHYL VANILLIN (121-32-4)	
Persistence and degradability	Readily biodegradable in water.

ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

ETHYL VANILLIN (121-32-4)

ThOD	1.81 g O ₂ /g substance
BOD (% of ThOD)	0.529 (5 day(s), Literature study)

2H-pyran-4-ol, tetrahydro-4-methyl-2-(2-methylpropyl)- (63500-71-0)

Persistence and degradability	Biodegradability in water: no data available.
-------------------------------	---

VANILLIN (121-33-5)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

12.3. Bioaccumulative potential

BENZYL BENZOATE (120-51-4)

BCF - Fish [1]	2.286 (BCFBAF v3.00, Pisces, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.97 (Experimental value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

2-Ethyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl)-2-buten-1-ol (28219-61-6)

BCF - Other aquatic organisms [1]	667 (Other, QSAR)
Partition coefficient n-octanol/water (Log Pow)	4.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 35 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

LINALYL ACETATE (115-95-7)

Partition coefficient n-octanol/water (Log Pow)	3.93 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

ETHOXYMETHYL CYCLODODECYL ETHER (58567-11-6)

BCF - Fish [1]	530 – 560 (OECD 305: Bioconcentration: Flow-Through Fish Test, 28 day(s), Cyprinus sp., Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.4 (Experimental value, OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method, 25 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

COUMARIN (91-64-5)

Partition coefficient n-octanol/water (Log Pow)	1.39 (QSAR, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Dihydromyrcenol (18479-58-8)

Partition coefficient n-octanol/water (Log Pow)	3.47 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

ETHYL VANILLIN (121-32-4)

Partition coefficient n-octanol/water (Log Pow)	1.58 (Experimental value, Equivalent or similar to OECD 107, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

2H-pyran-4-ol, tetrahydro-4-methyl-2-(2-methylpropyl)- (63500-71-0)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

VANILLIN (121-33-5)

Partition coefficient n-octanol/water (Log Pow)	1.17 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

BENZYL BENZOATE (120-51-4)

Surface tension	0.027 N/m (210 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.

2-Ethyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl)-2-buten-1-ol (28219-61-6)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.57 (log Koc, Other, QSAR)
Ecology - soil	Low potential for adsorption in soil.

ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

LINALYL ACETATE (115-95-7)	
Ecology - soil	Adsorbs into the soil.
ETHOXYMETHYL CYCLODODECYL ETHER (58567-11-6)	
Surface tension	Data waiving
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.73 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Adsorbs into the soil.
COUMARIN (91-64-5)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.63 (log Koc, QSAR)
Ecology - soil	Highly mobile in soil.
Dihydromyrcenol (18479-58-8)	
Ecology - soil	No (test)data on mobility of the substance available.
ETHYL VANILLIN (121-32-4)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.092 (log Koc, Equivalent or similar to OECD 106, Experimental value)
Ecology - soil	Low potential for mobility in soil.
2H-pyran-4-ol, tetrahydro-4-methyl-2-(2-methylpropyl)- (63500-71-0)	
Ecology - soil	No (test)data on mobility of the substance available.
VANILLIN (121-33-5)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.438 (log Koc, Experimental value)
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT)	: UN3082 Environmentally hazardous substances, liquid, n.o.s. (BENZYL BENZOATE ; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8-tetramethyl-2-naphthalenyl)ethanone (Iso E Super)), 9, III
UN-No. (DOT)	: UN3082
Proper Shipping Name (DOT)	: Environmentally hazardous substances, liquid, n.o.s. BENZYL BENZOATE ; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8-tetramethyl-2-naphthalenyl)ethanone (Iso E Super)
Class (DOT)	: 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140
Packing group (DOT)	: III - Minor Danger

ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Hazard labels (DOT)	: 9 - Class 9 (Miscellaneous dangerous materials)
	
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies. 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination. 173 - An appropriate generic entry may be used for this material. 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 155
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: No Limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: No Limit
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 171
Other information	: No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran	CAS-No. 1222-05-5	5 – 10%

SECTION 16: Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

ANTIQUE SANDALWOOD DUPLICATION

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements:

H227	Combustible liquid
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H336	May cause drowsiness or dizziness

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.