

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 10/21/2019 Revision date: 05/22/2025 Supersedes: 05/14/2025

Version: 2.2

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : BLACK RASPBERRY VANILLA BBW TYPE

CAS-No. : MIXTURE Product code : #215765

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

1.4. Emergency telephone number

Emergency number : INFOTRAC (US & Canada) 1-800-535-5053 | (International) 1-352-323-3500

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin sensitization, H317 May cause an allergic skin reaction

Category 1

Reproductive toxicity H361 Suspected of damaging fertility or the unborn child

Category 2

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Warning

Hazard statements (GHS US) : H317 - May cause an allergic skin reaction

H361 - Suspected of damaging fertility or the unborn child

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of water.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

05/22/2025 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification	
BENZYL BENZOATE	(CAS-No.) 120-51-4	10 – 30	Acute Tox. 4 (Oral), H302	
HEXYL CINNAMAL	(CAS-No.) 101-86-0	5 – 10	Skin Sens. 1B, H317	
LINALYL ACETATE	(CAS-No.) 115-95-7	1 – 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Skin Sens. 1B, H317	
LIMONENE	(CAS-No.) 5989-27-5	1 – 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304	
LINALOOL	(CAS-No.) 78-70-6	1 – 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1B, H317	
p-Mentha-1,4-diene	(CAS-No.) 99-85-4	< 0.5	Flam. Liq. 3, H226 Repr. 2, H361 Asp. Tox. 1, H304	

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : May cause an allergic skin reaction. Symptoms/effects after eye contact : None under normal conditions. Symptoms/effects after ingestion : None under normal conditions.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material-damage.

05/22/2025 EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to

prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective

handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated

clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Store locked up.

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

BENZYL BENZOATE (120-51-4)

Not applicable

Linalool (78-70-6)

Not applicable

LINALYL ACETATE (115-95-7)

Not applicable

D-LIMONENE (5989-27-5)

Not applicable

HEXYL CINNAMIC ALDEHYDE (101-86-0)

Not applicable

p-Mentha-1,4-diene (99-85-4)

Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

05/22/2025 EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available

Flash point : ≈ 94.3 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability Not applicable. Vapor pressure : No data available Relative vapor density at 20°C : No data available Relative density : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) No data available Auto-ignition temperature : No data available Decomposition temperature : No data available No data availableViscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** No data available : No data available Explosive properties Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

05/22/2025 EN (English US) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

BENZYL BENZOATE (120-51-4)		
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	> 2 ml/kg (Modification of Draize 1959 method, 4 h, Rabbit, Experimental value, Dermal)	
ATE US (oral)	1160 mg/kg body weight	
Linalool (78-70-6)		
LD50 oral rat	2790 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	5610 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 7 day(s))	
ATE US (oral)	2790 mg/kg body weight	

D-LIMONENE (5989-27-5)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Read-across, Oral)
LD50 dermal rabbit	> 5000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Weight of evidence, Dermal)

5610 mg/kg body weight

ATE US (oral) 3100 mg/kg body weight

p-wentna-1,4-diene	(99-85-4)
ATE US (arel)	

ATE US (oral) 3650 mg/kg body weight

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

D-LIMONENE (5989-27-5)

ATE US (dermal)

IARC group 3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

05/22/2025 EN (English US) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Linalool (78-70-6)	
NOAEL (dermal,rat/rabbit,90 days)	250 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

SECTION 12: Ecological information

12 1		OX	

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

BENZYL BENZOATE (120-51-4)		
LC50 - Fish [1]	2.32 mg/l (EU Method C.1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)	
EC50 - Crustacea [1]	3.09 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	
Linalool (78-70-6)		
LC50 - Fish [1]	27.8 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, GLP)	
EC50 - Crustacea [1]	59 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	
ErC50 algae	156.7 mg/l (DIN 38412-9, 96 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)	
LINALYL ACETATE (115-95-7)		
LC50 - Fish [1]	11 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Cyprinus carpio)	
EC50 - Crustacea [1]	15 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna)	
D-LIMONENE (5989-27-5)		
LC50 - Fish [1]	720 µg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)	
EC50 - Crustacea [1]	0.36 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	

12.2. Persistence and degradability

BENZYL BENZOATE (120-51-4)		
Persistence and degradability	Readily biodegradable in water.	
Linalool (78-70-6)		
Persistence and degradability	Readily biodegradable in water.	
LINALYL ACETATE (115-95-7)		
Persistence and degradability	Readily biodegradable in water.	
D-LIMONENE (5989-27-5)		
Persistence and degradability	Readily biodegradable in water.	
ThOD	3.29 g O₂/g substance	

12.3. Bioaccumulative potential

BENZYL BENZOATE (120-51-4)		
BCF - Fish [1]	2.286 (BCFBAF v3.00, Pisces, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (Experimental value, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

05/22/2025 EN (English US) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Linalool (78-70-6)		
Partition coefficient n-octanol/water (Log Pow)	2.84 (Experimental value, Equivalent or similar to OECD 107, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
LINALYL ACETATE (115-95-7)		
Partition coefficient n-octanol/water (Log Pow)	3.93 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
D-LIMONENE (5989-27-5)		
BCF - Fish [1]	864.8 – 1022 (Pisces, QSAR, Fresh weight)	
Partition coefficient n-octanol/water (Log Pow)	4.38 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 37 °C)	
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).	

12.4. Mobility in soil

BENZYL BENZOATE (120-51-4)		
Surface tension	0.027 N/m (210 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)	
Ecology - soil	Low potential for mobility in soil.	
Linalool (78-70-6)		
Surface tension	8.3 mN/m (20 °C, ISO 9101: Surface active agents - Determination of interfacial tension)	
Ecology - soil	No (test)data on mobility of the substance available.	
LINALYL ACETATE (115-95-7)		
Ecology - soil	Adsorbs into the soil.	
D-LIMONENE (5989-27-5)		
Ecology - soil	Adsorbs into the soil.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1.	Disposal	methods
-------	----------	---------

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN3082 Environmentally hazardous substances, liquid, n.o.s. (BENZYL BENZOATE;

1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran), 9, III

UN-No.(DOT) : UN3082

Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s.

BENZYL BENZOATE; 1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-

benzopyran

Class (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140

Packing group (DOT) : III - Minor Danger

05/22/2025 EN (English US) 7/9

Safety Data Sheet

Hazard labels (DOT)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5 5 7



: 203

: 241

DOT Packaging Non Bulk (49 CFR 173.xxx)

DOT Packaging Bulk (49 CFR 173.xxx)

DOT Symbols

DOT Special Provisions (49 CFR 172.102)

: G - Identifies PSN requiring a technical name

: 9 - Class 9 (Miscellaneous dangerous materials)

: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.

146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.

173 - An appropriate generic entry may be used for this material.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 155

DOT Quantity Limitations Passenger aircraft/rail : No Limit

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : No Limit

CFR 175.75)

DOT Vessel Stowage Location

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Emergency Response Guide (ERG) Number

Other information

: No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopentagamma-2-benzopyran CAS-No. 1222-05-5 10 – 30%

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/22/2025

05/22/2025 EN (English US) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H361	Suspected of damaging fertility or the unborn child

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

05/22/2025 EN (English US) 9/9