

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 04/11/2025 Revision date: 04/23/2025 Supersedes: 04/11/2025

Version: 1.1

## **SECTION 1: Identification**

1.1. Identification

Product form : Mixture

Product name : OATMEAL MILK AND HONEY

CAS-No. : MIXTURE Product code : #296331

#### 1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

### 1.4. Emergency telephone number

Emergency number : INFOTRAC (US & Canada) 1-800-535-5053 | (International) 1-352-323-3500

### SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Skin sensitization, H317 May cause an allergic skin reaction

Category 1

Full text of H statements : see section 16

### 2.2. GHS Label elements, including precautionary statements

### **GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H317 - May cause an allergic skin reaction

Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### **SECTION 3: Composition/Information on ingredients**

### 3.1. Substances

Not applicable

## 3.2. Mixtures

Name	Product identifier	%	GHS US classification
BENZYL BENZOATE	(CAS-No.) 120-51-4	10 – 30	Acute Tox. 4 (Oral), H302

04/23/2025 EN (English US) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
COUMARIN	(CAS-No.) 91-64-5	5 – 10	Acute Tox. 3 (Oral), H301 Skin Sens. 1B, H317
BENZALDEHYDE	(CAS-No.) 100-52-7	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Irrit. 2A, H319 STOT SE 3, H335
ETHYL VANILLIN	(CAS-No.) 121-32-4	1 – 5	Eye Irrit. 2B, H320

Full text of hazard classes and H-statements : see section 16

### **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : None under normal conditions.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

04/23/2025 EN (English US) 2/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled r

: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed

: Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling

: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated

clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Keep cool. Protect from sunlight.

Packaging materials : Store always product in container of same material as original container.

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### ETHYL VANILLIN (121-32-4)

Not applicable

### **BENZYL BENZOATE (120-51-4)**

Not applicable

### BENZALDEHYDE (100-52-7)

Not applicable

### **COUMARIN (91-64-5)**

Not applicable

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment

## 8.3. Individual protection measures/Personal protective equipment

### Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

### Skin and body protection:

Wear suitable protective clothing

## Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

04/23/2025 EN (English US) 3/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Personal protective equipment symbol(s):







### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available

Flash point : > 100 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability : Not applicable. Vapor pressure No data available Relative vapor density at 20°C : No data available : No data available Relative density Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature No data available : No data available Decomposition temperature No data availableViscosity, kinematic : No data available Viscosity, dynamic No data available : No data available **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties

### 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No additional information available

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

04/23/2025 EN (English US) 4/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ETHYL VANILLIN (121-32-4)	
LD50 oral rat	> 3160 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
ATE US (oral)	3000 mg/kg body weight
RENZVI RENZOATE (120.51.4)	

BENZYL BENZOATE (120-51-4)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2 ml/kg (Modification of Draize 1959 method, 4 h, Rabbit, Experimental value, Dermal)
ATE US (oral)	1160 mg/kg body weight

BENZALDEHYDE (100-52-7)	
LD50 oral rat	1300 mg/kg (Rat, Oral)
LD50 dermal rat	> 1250 mg/kg (Rat, Dermal)
LD50 dermal rabbit	5000 mg/kg (Rabbit, Dermal)
ATE US (oral)	1300 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

COUMARIN (91-64-5)	
LD50 oral rat	293 mg/kg body weight (Rat, Male / female, Experimental value, Oral)
ATE US (oral)	290 mg/kg body weight

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

COUMA	RIN (91-64-5)	
IARC gro	oup	3 - Not classifiable

Reproductive toxicity : Not classified STOT-single exposure : Not classified

BENZALDEHYDE (100-52-7)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : May cause an allergic skin reaction. Symptoms/effects after eye contact : None under normal conditions. Symptoms/effects after ingestion : None under normal conditions.

## **SECTION 12: Ecological information**

12.1.	Tox	icity
-------	-----	-------

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse
	effects in the environment

04/23/2025 EN (English US) 5/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHYL VANILLIN (121-32-4)	
LC50 - Fish [1]	87.6 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 - Crustacea [1]	36.79 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Read-across, GLP)
ErC50 algae	120 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)
BENZYL BENZOATE (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (EU Method C.1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	3.09 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
BENZALDEHYDE (100-52-7)	
LC50 - Fish [1]	11.2 mg/l (96 h, Salmo gairdneri, Flow-through system)
EC50 - Crustacea [1]	50 mg/l (24 h, Daphnia magna)
COUMARIN (91-64-5)	
LC50 - Fish [1]	2.94 mg/l (96 h, Pisces, QSAR)
EC50 - Crustacea [1]	24.3 – 36.9 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, GL

#### 12.2. Persistence and degradability

ETHYL VANILLIN (121-32-4)		
Persistence and degradability	Readily biodegradable in water.	
ThOD	1.81 g O₂/g substance	
BOD (% of ThOD)	0.529 (5 day(s), Literature study)	
BENZYL BENZOATE (120-51-4)		
Persistence and degradability	Readily biodegradable in water.	
BENZALDEHYDE (100-52-7)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.62 g O₂/g substance	
Chemical oxygen demand (COD)	1.98 g O₂/g substance	
ThOD	2.42 g O₂/g substance	
BOD (% of ThOD)	0.67	
COUMARIN (91-64-5)		
Persistence and degradability	Readily biodegradable in water.	

## 12.3. Bioaccumulative potential

ETHYL VANILLIN (121-32-4)			
1.58 (Experimental value, Equivalent or similar to OECD 107, 25 °C)			
Low potential for bioaccumulation (Log Kow < 4).			
BENZYL BENZOATE (120-51-4)			
2.286 (BCFBAF v3.00, Pisces, QSAR)			
3.97 (Experimental value, 25 °C)			
Low potential for bioaccumulation (Log Kow < 4).			
4.2 – 7.8 (Estimated value)			
1.48 (Experimental value)			
Low potential for bioaccumulation (Log Kow < 4).			
1.39 (QSAR, 25 °C)			
Low potential for bioaccumulation (Log Kow < 4).			

## 12.4. Mobility in soil

04/23/2025 EN (English US) 6/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHYL VANILLIN (121-32-4)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.092 (log Koc, Equivalent or similar to OECD 106, Experimental value)
Ecology - soil	Low potential for mobility in soil.
BENZYL BENZOATE (120-51-4)	
Surface tension	0.027 N/m (210 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.
BENZALDEHYDE (100-52-7)	
Surface tension	0.04 N/m (20 °C)
COUMARIN (91-64-5)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.63 (log Koc, QSAR)
Ecology - soil	Highly mobile in soil.

#### 12.5. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

## **SECTION 14: Transport information**

## **Department of Transportation (DOT)**

In accordance with DOT

Transport document description (DOT) : UN3082 Environmentally hazardous substances, liquid, n.o.s. (1,3,4,6,7,8-Hexahydro-

4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran; BENZYL BENZOATE), 9, III

UN-No.(DOT) : UN3082

Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s.

1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran; BENZYL

BENZOATE

Class (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name

04/23/2025 EN (English US) 7/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.

146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.

173 - An appropriate generic entry may be used for this material.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

DOT Packaging Exceptions (49 CFR 173.xxx) : 155
DOT Quantity Limitations Passenger aircraft/rail : No Limit

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : No Limit

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Emergency Response Guide (ERG) Number :

Other information : No supplementary information available.

### **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 04/23/2025

04/23/2025 EN (English US) 8/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## Full text of H-phrases:

H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

04/23/2025 EN (English US) 9/9